

PTC-Sicherungen / PTC-Fuses

Abmessungen / Dimensions	4,8-13,5 x 9,3-14,6 mm	13,5 x 14,5 mm	5,7-28,5 x 10,5-32,5 mm	5,5-13,0x7,6 mm
Typ / Type	LB	LBV	LP 60	LBR
V max.	250 V	600 V	60 V	90 V
I max.	3 A - 10 A	3 A	40 A	20 A
I H	0,080 A - 0,180 A	0,150 A - 0,160 A	0,05 A - 3,75 A	0,20 A - 0,90 A
I T	0,160 A - 0,360 A	0,300 A - 0,320 A	0,10 A - 7,50 A	0,40 A - 1,80 A
Besonder- heiten / Features	runder Körper; ab IH 0,120 A rechteckiger Körper / round corpus; ex IH 0,120 A square corpus	rechteckiger Körper / square corpus	gesickte Drähte; ab IH 1,10 A gerade Drähte / kinked lead options; ex IH 1,10 A straight wires	runder Körper / round corpus

Abmessungen / Dimensions	6,0-24,5 x 13,8-36,4 mm	7,8-28,6 x 11,7-28,7 mm	6,4-11,5 x 11,4-20,4 mm	20,0-31,0 x 5,2-13,3 mm
Typ / Type	LP 30	LP 16	LP 06	LP
V max.	30 V	16 V	6 V	15 - 30 V
I max.	40 A	100 A	40 A	100 A
I H	0,90 A - 9,00 A	3,0 A - 14,0 A	0,75 A - 2,50 A	0,70 A - 4,20 A
I T	1,80 A - 18,00 A	5,1 A - 23,8 A	1,30 A - 5,00 A	1,45 A - 7,60 A
Besonder- heiten / Features	rechteckiger Körper / square corpus	rechteckiger Körper / square corpus	rechteckiger Körper; IH 0,75 A und 1,20 A runder Körper / square corpus; IH 0,75 A and 1,20 A round corpus	Streifen- Sicherung / Strip-Fuse

Abmessungen / Dimensions	17,5-43,0 x 3,8-17,3 mm	7,98-9,50 x 3,00-3,18 mm	4,73-11,51 x 3,41-5,33 mm
Typ / Type	LP-CW	LP-SM	LP-MSM
V max.	16 V	6 V - 60 V	6 V - 60 V
I max.	100 A	10 A - 40 A	10 A - 100 A
I H	1,70 A - 2,50 A	0,30 A - 3,00 A	0,10 A - 2,60 A
I T	3,40 A - 5,40 A	0,60 A - 6,00 A	0,20 A - 5,20 A
Besonder- heiten / Features	Streifen-Sicherung / Strip-fuse	Oberflächenmontage / Surface mount	Oberflächenmontage / Surface mount