




# JM162D

16 CHAR × 2 LINE  
1/16 DUTY, 1/5 BIAS

## 1 EXTERNAL DIMENSION



## 2 MECHANICAL DATA

ITEM	SPECIFICATION	UNIT
Module Size (W×H×T)	80.0×36.0×10.0 (LED:12.8)	mm
Viewing Area (W×H)	61.0×15.8	mm
Character Font (W×H)	5×7+cursor	dots
Character Size (W×H)	2.95×5.55	mm
Character Pitch (W×H)	3.55×5.95	mm
Dot Size (W×H)	0.55×0.65	mm

## 5 ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN.	MAX.	UNIT
Supply Voltage	Vdd	-0.3	7.0	V
LCD Supply Voltage	V5	Vdd-13.5	0	V
Input Voltage	Vi	-0.3	Vdd+0.3	V
Operating Temperature	Top	0	50	°C
Storage Temperature	Tstg	-20	70	°C


## 3 PIN CONNECTIONS

PIN	SYMBOL	SIGNAL DESCRIPTION
1	GND	Power Supply: 0V
2	Vdd	Power Supply: +5V
3	V5	Power Supply for LCD
4	RS	Register Select(H=DATA,L=Instruction)
5	R/W	Read/Write L=MPU to LCM,H=LCM to MPU
6	E	Enable
7 to 14	DB0 to DB7	Data Bus for 4bit or 8bit Mode
15	K	Cathode of LED Unit
16	A	Anode of LED Unit

## 6 ELECTRICAL CHARACTERISTICS (Ta=25°C)

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage (logic)	Vdd-GND	-	4.5	5.0	5.5	V
Supply Current(logic)	Idd	Vdd=5.0V	-	1.5	3.0	mA
Driving Current(LCD)	Iee		-	0.4	1.0	mA
Driving Voltage(LCD)	Vdd-V5		3.8	4.5	4.9	V
Input Voltage "H"	Vih		2.2	-	Vdd	V
Input Voltage "L"	Vil	-0.3	-	0.6	V	
Output Voltage "H"	Voh	Ioh=-0.205mA	2.4	-	-	V
Output Voltage "L"	Vol	Iol=1.2mA	-	-	0.4	V

## 4 BLOCK DIAGRAM



## 7 BOTTOM BACKLIGHT CHARACTERS (Ta=25°C)

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage	VLED	-	-	4.2	-	V
LED Forward Consumption Current	If	If=200mA Vf=4.2V	-	83	-	mA
LED Allowable Dissipation	Pd	-	-	350	-	mW